

RC Column Cyclic Tests

**Fu-Pei, Hsiao, Wen-Cheng, Shen,
Pu-Wen, Weng, Yi-An, Li**

Sep. 15, 2018

Outlines


- **Specimen Design**
- **Construction**
- **Test Setup**
- **Instrumentation Scheme**
 - Interior
 - Exterior
- **Material Property**
- **Test Result**

Specimen Design

Cross Section of Members

$$\rho_s = 2.53\%$$


Column A



Longitudinal Rebar: 8-D19
 Stirrups: D10@12 cm
 Crossties: D10@24 cm

Stirrups: 90° Hook, Staggered
 Crossties: 135° and 90° Hooks, Staggered
 Cover: 2 cm

Column B




Longitudinal Rebar: 20-D19
 Stirrups: D10@12 cm
 Crossties: D10@24 cm

Stirrups: 90° Hook, Staggered
 Crossties: 135° and 90° Hooks, Staggered
 Cover: 2 cm


Column A (30×30)

Aspect Ratio ≈ 8.66



Column B (30x75)

Aspect Ratio ≈ 8.66



Specimen Construction

Specimen Construction



Rebar Installation Completed



Formwork Assembly Completed




Construction Completed


Instrumentation Scheme

- Interior
- Exterior

Column A (30x30)



Total 45
Longitudinal: 24
Hoop: 21



Section B-B

↔
 Loading Direction

Longitudinal	Hoop
Stain Gage A: 7	Stain Gage E: 11
Stain Gage B: 7	Stain Gage G: 4
Stain Gage C: 3	Tie
Stain Gage D: 7	Stain Gage F: 6
Total 45	

Front View

Right Side View

Left Side View

Back View

Strain Gage C, E



Strain Gage A, B, F

Strain Gage D, F

Strain Gage G

Column B (30x75)

Total 45
Longitudinal: 24
Hoop: 21



Section B-B



Loading Direction

- | | |
|---------------------|------------------|
| Longitudinal | Hoop |
| Stain Gage A: 7 | Stain Gage E: 11 |
| Stain Gage B: 7 | Stain Gage G: 4 |
| Stain Gage C: 3 | |
| Stain Gage D: 7 | Tie |
| | Stain Gage F: 6 |
| Total 45 | |

Front View

Right Side View

Left Side View

Back View

Strain Gage C, E


Stain Gage A, B, F

Stain Gage D, F

Strain Gage G


Exterior Instrument

Loading Direction



Test Setup


Loading Protocol



Column A $P \approx 0.12 A_g f'_c$

Column B $P \approx 0.06 A_g f'_c$


Cyclic test in constant axial load P



Material Property


Yield Strength of Steel

- **D10** vs. **D19**



Compression Strength of Concrete

28 Days	f'_c (kgf/cm ²)
Specimen 1	210.16
Specimen 2	220.84
Specimen 3	227.83
Average	219.61




Compression Strength of Concrete

32 Days	f'_c (kgf/cm ²)
Specimen 4	222.88
Specimen 5	240.70
Specimen 6	246.21
Average	236.60



Compression Strength of Concrete


35 Days	f'_c (kgf/cm ²)
Specimen 7	239.43
Specimen 8	227.41
Specimen 9	238.77
Average	235.20




Test Results

- **Column A**
- **Column B**


Hysteretic Loop (Column A)




Crack Pattern (Column A)



Hysteretic Loop (Column B)



Crack Pattern (Column B)



Start




*$V_{max} = 225.24 \text{ kN}$
(Drift Ratio = 3%)*



*Final
(Drift Ratio = 4%)*

Hysteretic Loop

- **Column A** vs. **Column B**



**Thanks for your kind
attentions**